



BVCert. 6010761




EAN Code : 3543290003629

Oxygen



Range : Oxygen
 Function : Ageing (I-temperature)
 Reference : OXPIT98NVD
 Equipment : 2 Shelves (1 storing shelf and 1 sliding shelf)
 Capacity* : 98 Bottles*

Configuration



Bottles capacity with the standard configuration; 2 shelves : **98 Bottles***

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	5	74
Standard Configuration	1	1	98

* Traditional Bordeaux bottles

- Homogenous constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.
- Humidity rate between 65% and 80% ensuring by our product design, the cooling and venting system,
- The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.
- Ideal protection against UV rays thanks to our glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.
- No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions H x W x D (mm):	960 x 680 x 690	Weight cabinet empty (kg) :	52
Dimensions in pack (mm) :	1090 x 720 x 760	Weight equipped cabinet (kg) :	57,2
Colors :	Black	Weight in pack (kg) :	70,2
Door:	Glass door silver frame	Useful volume (L) :	225

Equipment & Accessories

Equipment

- Glass door with silver frame, integrated handle in the glass frame.
- Glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.
- Lock
- Reversible door
- 2 adjustable feet
- Labels for the bottles identification

Accessories

Universal shelves: AOHU I
Code EAN : 3543290002783
Weight : 2,6
Bottles capacity per level : 12 *
Material : Solid beech wood.

Modular system : you can choose the shelf configuration :



Sliding shelf
« 12 bottles »



Presentation shelf
« 6+22 bottles »



Storing shelf
« 72 bottles »

The label holder allows you to identify your bottle quickly and easily



Suitable to store all types of bottles



Technical features

Control Panel

- Electronic regulation from 9°C to 15°C; one identical temperature inside the wine cabinet
- Inner electronic display, Red Leds screen
- Visual alarm for the temperature fault
- Temperature display
- Automatic Winter function

Performances

Cold production : Static cooling
 Hot production : Heating element
 Humidity: Ensure by the thermodynamical pump system
 Winter function: Automatic
 Gaz uses : R600a
 Recommended temperature range : From 0°C to 30 °C
 Climate class : SN
 Inner material: Aluminium
 Insulation type: PU foam
 Acoustic emissions (db(A)): 37
 Consumption Aec(kWh/ An)**: : 146
 Energy efficiency rating : A
 Consumption Aec(kWh/ An)**: : 143

* Traditional Bordeaux bottles

** Calculation based on the result obtained over 24 hrs in standard conditions (25°C / 77°F) Alimentation 230V 50Hz.

*** Comply with DEPARTMENT OF ENERGY – 10 CFR Part 430 – Energy Conservation Program: Energy Conservation Standards for Miscellaneous Refrigeration Products .Alimentation 115V 60Hz