



Manufactured in France

1 temperature cabinet

Small size

Premium Pack



Ideal for the conservation of wine on the short, medium and long term.

Technical Specifications

Equipment
Standard shelf



Sliding shelf
ACMS
12 bottles



Storage shelf
AXUH
77 bottles

Capacity 74 bottles*

Temperature

- Default setup temperature: 12°C / 54°F
- Temperature setting range from 6/ 43°F à 18°C/64°F

Design

- 2 door options: glass with black frame or solid with black frame
- Black control panel
- White interior lighting: 2 leds(ON/OFF)
- Central lock
- LED screen with touch-sensitive keys
- White screen display

Accessories

- 5 ACMS shelves
- Optional: set of 20 black aluminium plates + 1 erasable felt-tip marker Ref : ID20-STYLO
- 1 EuroCave keyring

Equipment

- Charcoal filter
- 2 adjustable feet at the front
- Clay ball humidity cassette
- Condensate drip tray at the back
- Air circulation fan

Regulation

- Electronic regulation
- Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
- Display of the real temperature inside the cabinet
- Automatic defrost
- Hygrometry display

Technologies

- Cold production:** Mixed air / Compressor R600a gas
- Cords:** CE/US/UK/JA/AU/CH/C6
- Heat production:** Resistance
- Heat release:** Automatic / Threshold: adjustable
- Inner material:** Aluminium
- Exterior coating material:** HPL panel (High pressure laminates)
- Insulation type:** Injected polyurethane foam (59mm)

*Traditional Bordeaux format

General features

	Glass door	Solid door
Empty wine cabinet net weight (kg)	60	52
Equipped cabinet net weight (kg)	68	60
Gross weight packaged (kg)*	81	73
Dimensions H x W x D (mm)	960 x 680 x 720**	960 x 680 x 720**
Dimensions packaged (mm)	1090 x 720 x 760	1090 x 720 x 760
Colour	Nero - RAL 9005	Nero - RAL 9005

**Incl. the separator at the back/ 690 mm without separator.

Energy efficiency & Consumption

Cords	230V-50Hz (R600a)		115V-60Hz (R600a)	
	Solid	Glass	Solid	Glass
Type of door				
Energy efficiency class	F	G	/	/
Annual energy consumption AEC (Kwh/year)	103	128	114	143
Sound emission (dB(A))	37	37	38	38
Sound emission Class	C	C	/	/
Ambient operating temperature (°C/°F)	0-35°C / 32-95°F	0-30°C / 32-86°F	0-35°C / 32-95°F	0-30°C / 32-86°F
Useful volume (litres)	209			

La Premiere, in a few words

The fundamental by EuroCave.

The Première wine cabinet is designed for multiple uses. Concealed beneath its bold lines lies all the brand's expertise. Take your first steps into the world of EuroCave.

