

A 1 temperature cabinet adjustable from 6°C to 18° to mature your wines in the best possible conditions.



**Code : LOXXPV3**

### Internal layout : SHELVES

**Storage shelf :** AXUHT

**Weight:** 1,8 kg

**Dimensions (WxDxH):** 535 x 525 x 28 mm

**Type of structure:** slats

**Number of bottles:** up to 77

**Material:** Solid Beechwood coated with an ecological water varnish.



« Storage »  
77 Bottles

**Sliding shelf :** ACUPHT

**Weight:** 4 kg

**Dimensions (WxDxH):** 533x529x27mm

**Type of structure:** table

**Number of bottles:** up to 12

**Material:** Steel and PS shock



« Sliding »  
12 Bottles

Pack Type (sliding + storage shelves)	Pack Sliding	Storage Capacity
92	74	91
1 storage 1 sliding	5 sliding	1 storage

\* Maximum capacity

\*\* Empty wine cabinet

\*\*\* Traditional Bordeaux bottles

\*\*\*\* With the rear stop, without the handle

Range : **PRESTIGE**  
 Model : **Loft Vintage Full Glass door**  
 Function : **Ageing**  
 Capacity\* : **92 Bottles\*\*\***

### TECHNICAL BENEFITS

Combine technology/ performances and protection of the environment.

New Full Glass door using two panes reinforced with argon gas that guarantee better isolation and better protection against UV rays.

A constant temperature thanks to a double hot-cold regulation.

Suitable hygrometry thanks to a warmer and wetter air supply.

Air circulation ensured by the principle of thermodynamic pump.

No vibration thanks to the slow-cycles compressor fixed on silent blocs.

Storage or sliding shelves. One shelf for all kind of bottles.

### GENERAL FEATURES

Gross weight, packaged (Kg)	65
Net weight (Kg)**	54
Dimensions in packaging H x W x D (mm)	1045x733x768
Dimensions H x W x D (mm)	960x680x720****

Energy efficiency rating	G
Acoustic emissions (dB(A))	37
Acoustic emissions class	C
Consumption per 24h (KWh)	0,35
Annual energy consumption (kWh/year)	128
Ambient temperature operating limit (°C)	0-30
Useful volume (L)	209

- ✓ Electronic regulation. (1T = 6-18°C).
- ✓ Internal temperature display on the digital screen.
- ✓ Low energy consumption (59mm PU foam).
- ✓ Visual alarms : Temperature sensor defect, Temperature level (if too high or too low), Hygrometry (when too low, for 1 temp. only).
- ✓ Lighting system: 3 options: Permanent lighting, Lighting when door opening, No lighting.
- ✓ Double Hot/ Cold circuit > Automatic « Winter function ».
- ✓ Hygrometry ensured by the principle of thermodynamic pump.
- ✓ Anti-UV protection 97% of UV rays are filtrated
- ✓ 2 adjustable feet (front).
- ✓ Lock system.
- ✓ Storage grid in the lower part.
- ✓ Black stainless steel handle. Removable.
- ✓ Reversible door
- ✓ Inner material: Stucco Aluminum.
- ✓ Compressor - R600a Gas.
- ✓ Colors : Black or Tobacco.

