



5 YEAR WARRANTY



- Manufactured in France
- 1 temperature cabinet
- Small size
- Service Pack

Built-in and flush-fitted, 1 temperature cabinet. Ideal for the conservation of wine on the short, medium and long term.

**Technical specifications**  
Capacity 28 bottles maximum\*

Equipment  
**Standard shelves**



Sliding shelf  
ACMSIB  
6 bottles



Sliding shelf  
ACMSIW  
6 bottles



Sliding wine service area  
ACMSERVB  
11 bottles



Sliding wine service area  
ACMSERWV  
11 bottles



Half shelf  
ACMSI-DEMI  
5 bottles

Equipment  
**Optional shelves**



Storage shelf  
AXIHB  
22 bottles



Storage shelf  
AXIHW  
22 bottles

**Temperature** · Default setup temperature: 12°C/54°F  
· Temperature setting range from 5°C to 20°C / 41- 68°F

**Design**

- 4 doors options: full glass door, stainless steel glass door, technical solid door, technical glass door (reversible integrated glass door with soft close and door stop)
- Lock (except technical door)
- LED screen with backlit capacitive keys
- Amber inner lighting: atmosphere lighting with the light strip and 2 LEDs
- 3 lighting options: permanent, open door, disabled
- Amber screen display

**Accessories**

- 2 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front)
- 1 half shelf and 1 sliding wine service area
- Light oak and black glossy front
- 6 removable bottles identifiers per sliding shelf
- 1 erasable felt-tip marker
- 1 microfiber cloth
- 1 key ring

**Equipment**

- Charcoal filter (with counter)
- Humidity cassette with clay ball
- Low-emissivity glass and argon gas between the 2 glasses (in glass door or full glass finish)
- 4 adjustable feet
- Condensate drip tray at the back

**Regulation**

- Electronic regulation
- Display of the real temperature inside the cabinet
- Possible humidity display
- Display standby mode, possible
- Visual and audible alarms: temperature fault, sensor fault and open door
- Visual alarms: humidity fault and carbon filter change
- Automatic defrost
- Frost protection thermostat (double protection)

**Technologies**

- Cold production:** Static/ Compressor R600a
- Cords:** CE/US/UK/JA/AU/CH/C6/CN
- Hot production:** Heating element
- Hot release:** Automatic/ threshold: adjustable
- Inner material:** Stucco aluminium
- Exterior coating material:** HDF (High Density Fiber) melamine-faced panels
- Insulation type:** PU Foam (59mm)

\*Traditional Bordeaux format

## General features

	Full Glass door	Stainless steel glass door	Technical glass door	Technical solid door
Empty wine cabinet net weight (kg)	54	54	53	50
Equipped cabinet net weight (kg)	64	64	63	60
Gross weight packaged (kg)	77	77	76	73
Dimensions H x W x D (mm)	810-880x557-594**x597	810-880x557 -594**x597	810-880x557-594**x597	810-880x557-594**x597
Dimensions packaged (mm)	980x645x630	980x645x630	980x645x630	980x645x630
Specific features of the decor panel	Thickness: 20mm maximum / Weight: 12kg maximum			

\*\*With fillers

## Energy efficiency & Consumption

Cords	230V-50Hz (R600a)	230V-50Hz (R600a)	230V-50Hz (R600a)
Type of door	Full Glass door	Stainless steel glass door/ technical	Technical solid door
Energy efficiency class	G	G	F
Annual energy consumption AEC (Kwh/year)	125	125	99
Sound emission (dB(A))	38	38	38
Sound emission Class	C	C	C
Ambient operating temperature (°C/°F)	12-35/54-95	12-35/54-95	12-35/54-95
Useful volume (litres)		94	

Inspiration, in a few words...

## Understated & Elegant

The heart of the home, the kitchen is no longer reserved just for cooking. A place to gather and spend time together, it is open to all the family and often friends too. The kitchen has become a place where good times are shared, things are created, ideas germinate and chemistry happens...

