

	The second	Manufactured	in France 1 temperature	e cabinet	Medium size	Premium Pack
	FRANCE FRANCE FRANCE FRANCE FRANCE FRANCE FRANCE FRANCE FRANCE	for the cons long term.	flush-fitted, 1 tem ervation of wine on pecifications	-		
		Capacity	59 bottles maximum*			
Equipment <b>Standard shelf</b>	~	Temperature	•Default setup temperature: 12°C/54°F •Temperature setting range from 5°C to 20°C / 41- 68°F			
Sliding shelf ACMSIB 6 bottles	Sliding shelf ACMSIW 6 bottles	Design	<ul> <li>2 doors option: full glass do stainless steel glass door (reversible integrated glass with soft close and door sto</li> <li>Lock</li> <li>LED screen with backlit capacitive keys</li> </ul>	li door L p) .3 c	Amber inner lightin ghtingwith the lig EDS under the co B lighting options: open door, disable Amber screen disp	ht strip and 2 ontrol panel permanent, ed
Equipment Optional shelves	~	Accessories	<ul> <li>9 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front) + grio</li> <li>Light oak and black glossy fr</li> </ul>	pe of 1 d ·1	removable bottle er sliding shelf erasable felt-tip n microfiber cloth key ring	
iding wine service area ACMSERVB 11 bottles	Sliding wine service area ACMSERVW 11 bottles	Equipement	•Charcoal filter (with counter •Humidity cassette with clay	ball ga	ow-emissivity glas as between the 2 adjustable feet ondensate drip tr	glasses
Storage shelf AXIHB 22 bottles	Storage shelf AXIHW 22 bottles	Regulation	<ul> <li>Electronic regulation</li> <li>Display of the real temperation</li> <li>inside the cabinet</li> <li>Possible humidity display</li> <li>Display standby mode, possible</li> </ul>	iure fa Vi ar Au Sible Fr	sual and audible a ult, sensor fault ar sual alarms: humio nd carbon filter cho utomatic defrost rost protection the louble protection)	dity fault ange ermostat
Half shelf ACMSI-DEMI 5 bottles		Technologies	Cold production: Cords: Hot production: Hot release: Inner material: Exterior coating materia Insulation type:	CE He Au Stu I: HE me	ntilated //US/UK/JA/AU/CH eating element tomatic/ threshol ucco aluminium DF (High Density Fi elamine-faced par	d: adjustable ber)

\*Traditional Bordeaux format

Insulation type:

PU Foam (59mm)

## General features

	Porte Full Glass	Stainless steel glass door
Empty wine cabinet net weight (kg)	72	73
Equipped cabinet net weight (kg)	90	91
Gross weight packaged (kg)	105	106
Dimensions H x W x D (mm)	1320-1390 x 557-594** x 597	1320-1390 x 557-594** x 597
Dimensions packaged (mm)	1480 x 645 x 630	1480 x 645 x 630

\*\*With fillers

## Energy efficiency & Consumption

Cords	230V-50Hz (R600a)	230V-50Hz (R600a)		
Type of door	Full Glass	Stainless steel glass door		
Energy efficiency class	G	G		
Annual energy consumption AEC (Kwh/year)	154	154		
Sound emission (dB(A))	38	38		
Sound emission Class	С	С		
Ambient operating temperature (°C/°F)	12-35/54-95	12-35/54-95		
Useful volume (litres)	182			

Inspiration, in a few words...

## Understated & Elegant

The heart of the home, the kitchen is no longer reserved just for cooking. A place to gather and spend time together, it is open to all the family and often friends too. The kitchen has become a place where good times are shared, things are created, ideas germinate and chemistry happens...



