EUROCAVE[®]

Inspiration

		Manufactured	in France	1 temperature cabin	et Large size	Service Pack
	on of the the termination of terminatio of termination of termination of termination of termination o			ted, 1 temperat		
		for the cons	ervation	of wine on the s	hort, mediun	nand
	YEAR WARRANTY	long term.				
		Technical s Capacity	pecifcati 88 bottles n	ONS naximum*		
Equipment		Temperature	•Default set	up temperature: 12°C/54	°F	
Standard shelves	~		•Temperatu	re setting range from 5°C	to 20°C / 41- 68°F	
Sliding shelf	Clicking chaf	Design	stainless st solid door (reversible	tions: full glass door, eel glass door, technical and technical glass door integrated glass door ose and door stop)	 Amber inner lighting: atmosphere lighting with the light strip and 2 LEDs 3 lighting options: permanent, open door, disabled 	
Sliding shelf ACMSIB 6 bottles	Sliding shelf ACMSIW 6 bottles			ot technical door)	•Amber screen dis	
	• 1		 LED screer capacitive l 	n with backlit Keys		
ing wine service area	Sliding wine service area	Accessories	 12 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front) 		 6 removable bottles identifiers per sliding shelf 1 erasable felt-tip marker 	
ACMSERVB 11 bottles	ACMSERVW 11 bottles		wine servic		1 microfiber cloth1 key ring	
00000			•Light oak a	nd black glossy front		
Half shelf ACMSI-DEMI		Equipement		lter (with counter) assette with clay ball	• Low-emissivity glass gas between the 2 glass door or full gl	glasses (in
5 bottles					•4 adjustable feet	av at the back
Equipment					•Condensate drip tr	at the Dack
Optional shelves	ٽ الاسڪ	Regulation	 Electronic regulation Display of the real temperature inside the cabinet 		 Visual and audible a fault, sensor fault an Visual alarms: humic and carbon filter charter 	d open door lity fault
			Possible humidity display	and carbon filter cha · Automatic defrost	inge	
Storage shelf AXIHB	Storage shelf			ndby mode, possible	• Frost protection the (double protection)	
22 bottles	AXIHW 22 bottles	Technologies	Cold prod	uction:	Ventilated	
			Cords:		CE/US/UK/JA/AU/CH	/C6/CN
			Hot produ		Heating element	d. adjustable
			Hot releas		Automatic/ threshol Stucco aluminium	u. aujustable
				oating material:	HDF (High Density Fi melamine-faced pan	oer)
			Insulation	type:	PU Foam (59mm)	

General features

	Full Glass door	Stainless steel glass door	Technical glass door	Technical solid door
Empty wine cabinet net weight (kg)	91	92	87	80
Equipped cabinet net weight (kg)	122	123	118	111
Gross weight packaged (kg)	138	139	133	127
Dimensions H x W x D (mm)	1820-1890 x 557-594** x 597	1820-1890 x 557-594** x 597	820-1890 x 557-594** x 597	1820-1890 x 557-594** x 597
Dimensions packaged (mm)	1980 x 645 x 630	1980 x 645 x 630	1980 x 645 x 630	1980 x 645 x 630
Specificities of the decor panel		Thickness	:: 20mm maximum / Weight: 12kg	maximum

**With fillers

Energy efficiency & Consumption

Cords	230V-50Hz (R600a)	230V-50Hz (R600a)	230V-50Hz (R600a)	
Type of door	Full Glass	Stainless steel glass door/technical	Technical solid door	
Energy efficiency class	G	G	G	
Annual energy consumption AEC (Kwh/year)	176	176	136	
Sound emission (dB(A))	38	38	38	
Sound emission Class	С	С	С	
Ambient operating temperature (°C/°F)	12-35/54-95	12-35/54-95	12-35/54-95	
Useful volume (litres)		273		

Inspiration, in a few words...

Understated & Elegant

The heart of the home, the kitchen is no longer reserved just for cooking. A place to gather and spend time together, it is open to all the family and often friends too. The kitchen has become a place where good times are shared, things are created, ideas germinate and chemistry happens...



