EUROCAVE









SHELVES





Main du sommelier Anti-vibration technology







1 AOPRESAR + 1 ACMS 32 bottles capacity*

EUROCAVE'S ADVANTAGES

Temperature: Above-average insulation ensures that your wine cellar maintains a constant temperature, allowing your wine to reach its full potential.



Hygrometry: Its 6 cm insulation allows the compressor to start up less often, and therefore to dry out your cellar less.

Absence of vibration: Like a jewel box, the "Main Du Sommelier" supports hug and isolate each bottle from any disturbance (antivibration technology).

Air circulation: Constant air renewal prevents mold in your cellar. EuroCave cellars benefit from a 100% active window well ventilation system, making them very similar to natural cellar ventilation.

Darkness: Ultraviolet (UV) rays in natural and artificial light are harmful to wine. That's why EuroCave offers you solid or glass doors with double anti-UV thermos to protect your bottles.



INCLUDED ACCESSORIES



charcoal filter



Moisture case with clay balls



drip tray



Keychain



LA PREMIERE

MODEL: VPRE2LPV11

SIZE	&	CAPACITY

SIZE	Large
CAPACITY	166 bottles*
CONFIGURATION	11 ACMS sliding shelves 1 AOPRESAR presentation shelf

TEMPERATURE SETTINGS

TEMPERATURE ZONE	1 zone
TEMPERATURE RANGE	6°C to 18°C / 42°F to 64°F

DIMENSIONS & WEIGHT

DIMENICIONIC	H 71 %" x W 26 ¾" x D 27 ¼"*2
DIMENSIONS	H 1825mm x W 680mm x D 690mm* ²

DECLIDED BLILLT IN DIMENSIONS	H 72 ¾" x W 28 ¾" x D 28 ¾" H 1851mm x W 730mm x D 728mm
REQUIRED BUILT-IN DIMENSIONS	H 1851mm x W 730mm x D 728mm

WEIGHT 276 lbs / 125 kg

TECHNICAL SPECIFICATIONS

BUILT-IN & FREE-STANDING	Yes
DOOR TYPE	Double-thermos (argon) anti-UV glass, with black steel frame and joint
REVERSIBLE DOOR	Yes
SECURITY LOCK	Yes
LIGHTING	LED Cold white
ACTIVE CHARCOAL FILTER	100% active
	Probe problem
ALARMS	Temperature default
ALARMS	Humidity default
	Charcoal filter change (365 days)
CONTROL PANEL	Touch-sensitive LED display
SHELVES	Ball-bearing slides
INTERIOR WALLS	Embossed aluminum
EXTERIOR CLADDING	Black laminate panel
ISOLATION	Polyurethane foam 6cm thick
ACOUSTIC EMISSION	38 dB(A)
VENTILATION TYPE	Internal air circulation fan
COMPRESSOR	Embraco Inverter - R600a gas

^{*} Capacities are approximate and calculated using traditional Bordeaux-type bottles

MODEL: VPRE2LPV11