

A 3 temperature cabinet offering 3 zones made for ageing, chambering and cooling.



Code: CA3TGV3

Internal layout: SHELVES

Storage shelf: AXUHT

Weight: 1,8 kg

Dimensions (WxDxH): 535 x 525 x 28 mm

Type of structure: slats **Number of bottles**: up to 77

Material: Solid Beechwood coated with an ecological water varnish.



« Storage» 77 Bottles

Sliding shelf: ACUPHT

Weight: 4 kg

Dimensions (WxDxH): 533x529x27mm

Type of structure: table
Number of bottles: up to 12
Material: Steel and PS shock



«Sliding»

Pack Type (sliding + storage shelves)	Pack Sliding	Storage Capacity
190	165	209
3 storage 3 sliding	10 sliding	3 storage

* Maximum capacity

** Empty wine cabinet

*** Traditional Bordeaux bottles

**** With the rear stop, without the handle.

Range: PRESTIGE

Model : Castel Glass door

Function: Service and Ageing

Capacity*: 209 Bottles***

Combine technology/ performances and protection of the

environment.

TECHNICAL BENEFITS

A constant temperature thanks to a double hot-cold regulation.

New glass door with double panel reinforced with Argon gas for a better insulation and to filter up to 97% of U.V. rays. It will also lower the condensation risks.

Suitable hygrometry thanks to a warmer and wetter air supply.

Air circulation ensured by the principle of thermodynamic pump.

No vibration thanks to the slow-cycles compressor fixed on silent blocs

Storage or sliding shelves.

GENERAL FEATURES

Gross weight, packaged(Kg)	106
Net weight (Kg)**	97
Dimensions in packaging H x W x D (mm)	1910x733x768
Dimensions H x W x D (mm)	1825x680x720****
Energy efficiency rating	G
Acoustic emissions (dB(A))	37
Acoustic emissions class	С
Consumption per 24h (KWh)	0,48
Annual energy consumption Aec (kWh/year)	176
Ambient temperature operating limit (°C)	12-30
Useful volume (L)	446

- ✓ Electronic regulation.
- ✓ Internal temperature display on the digital screen.
- ✓ Low energy consumption (59mm PU foam).
- \checkmark Visual alarms: Temperature sensor defect, Temperature level (if too high or too low).
- \checkmark Lighting system: 3 options: Permanent lighting, Lighting when door opening, No lighting.
- ✓ Double Hot/ Cold circuit.
- ✓ Hygrometry ensured by the principle of thermodynamic pump.
- √ Anti-UV protection (for glass door only).
- √ 2 adjustable feet(front).
- ✓ Lock system.
- \checkmark Storage grid in the lower part.
- ✓ Black and Silver stainless steel handle. Removable.
- ✓ Reversible door (glass door only).
- ✓ Inner material: Stucco Aluminum.
- ✓ Compressor R600a Gas.
- ✓ Colors : Black or Tobacco.

